

## Condenser Gooseneck Conference Microphone

### ITS-220/ITS-330/ITS-410/ITS-450/ITS-485



#### Feature

- \* Pre-polarized condenser basemounted gooseneck
- \* Microphone length 220mm/330mm/410mm/450mm/485mm
- \* Radio frequency interference
- \* It has cardioid pattern with 120 degree angle
- \* Designed for high-quality sound reinforcement, professional recording and broadcasting
- \* Mount design with 3-pin XLR/RJ45-type connector
- \* Included shock mount
- \* LED Indicator (optional)
- \* Complete conference room solution

#### Specifications:

<b>Model</b>	ITS-220/ITS-330/ITS-410/ITS-450/IT-485
<b>Directional characteristics</b>	Bunch
<b>Interface</b>	Balanced 3 Pin- XLR/RJ45 (optional) interface
<b>Sensitivity (at 1kHz)</b>	7 mV/Pa
<b>Frequency response</b>	20Hz-20kHz
<b>Attenuation</b>	-10dB(-12dB Butwrth)
<b>Limit SPL (1 %THD@1 kHz)</b>	137dB
<b>Equivalent SPL (according to IEC 651)</b>	19 dB-A
<b>SNR</b>	78 dB
<b>Rated impedance</b>	100Ω
<b>Rated terminal impedance</b>	>1 kΩ
<b>Phantom power</b>	+48V
<b>Power consumption</b>	3mA

Note: Image are subject to change without prior notice for enhancement of product's specification.