



*Using 1pc mid-bass speaker unit and 1pcs Circular polyethylene diaphragm compression tweeter unit.

*The box is made of 15mm plywood, light quality, with wear resistant paint processing, and paste dust-proof mesh cotton outside.

*Frequency divider in precise design is used to optimize power response and MF vocal performance.

*Multiple screw lifting holes, 35 mm cylinder socket, multiple installation methods.

*Work with professional power amplifier, pre-effect processor together, formed a set of perfect sound, vocal performance outstanding high-end entertainment meeting sound-reinforcement system, suitable for KTV rooms, luxury meeting rooms and multi-function hall and other places for use,It can also be matched with subwoofer high-performance satellite box.

Model	TS-608A	TS-610	TS-612	TS-615
Impedance	8Ω	8Ω	8Ω	8Ω
Frequency Response	65Hz~20KHz	55Hz~20KHz	50Hz~20KHz	45Hz~20KHz
Rated Power	150W	300W	350W	450W
Peak Power	600W	1200W	1400W	1800W
Sensitivity	95dB/W/M	98dB/W/M	99dB/W/M	100dB/W/M
Max Spl (Rated/Peak)	117dB/123dB	123dB/129dB	124dB/131dB	127dB/133dB
Coverage Angle	(H)80° (V)60°	(H)80° (V)60°	(H)80° (V)60°	(H)80°(V)60°
Tweeter	3" compression tweeter x2	1.4"Compressed treble unit x 1	1.7"Compressed treble unit x1	1.73"Compressed treble unit x 1
Bass	8"woofer x1	10"x1 Bass	12" x 1 Bass	15" x 1 Bass
Dimension	385 x 24x 243mm	510 x 325 x 300 mm	560 x 360 x 380mm	660 x 435 x 430 mm
Weight	7.8Kg	15.2Kg	19.2Kg	25.8Kg