



- ✦ Supports the latest H.265 video encoding and decoding, achieving 4K30 ultra high definition video with a bandwidth of 2Mbps, ensuring high-quality video while reducing network construction and operation costs. Simultaneously possessing excellent dual stream collaboration capabilities, supporting dual 4K30+4K30.
- ✦ Supports 4 video inputs and 2 video outputs, 7 audio inputs and 5 audio outputs, supports 4K high-definition and H.265 encoding and decoding, with rich interfaces and flexible adaptation to various peripherals, meeting the needs of large and medium-sized conferences and industries.
- ✦ Supports two high-definition video outputs, and can be connected to two large screen display devices at the same time. According to the conference scene, two large screen display devices can simultaneously output different images, improving the conference experience.
- ✦ Supports real-time live streaming of meetings through RTMP streaming to live streaming platforms, and supports streaming from live streaming platforms to terminal playback. The terminal supports streaming input through the network camera RTSP.
- ✦ In addition to supporting remote recording and playback, it also supports USB flash drive recording, plug and play, USB Pass-through and secure and confidential meeting records.

*Picture for illustration purpose only



Specifications:

Standards & Protocol	
Multimedia Framework Protocol	ITU-T H.323,IETF SIP
Video Codec Protocol	H.265, H.264 HP,H.264
Audio Codec Protocol	G.711, G.722, G.722.1, G.722.1C, AAC-LD, G.726, SILK
Double Stream Protocol	ITU-T H.239, IETF BFCP
Other Communication Protocols	H.221, H.224, H.225, H.235, H.241, H.245, H.281, H.350, H.460, T.140, DTMF
Network Transmission Protocols	TCP/IP, DHCP, SSH, HTTP, HTTPS with SSL/TLS, RTP, RTCP, RFC3261, RFC3264, RFC2190, RFC3407, RFC2833, RFC4585(RTP/AVPF), SNTP, ARP
Video Features	
First Stream Resolution	4K30, 4K15, 1080P60, 1080P30, 720P60, 720P30
Second Stream Resolution	HDMI In: VGA (640×480) 60fps、 SVGA (800×600) 60fps、 XGA(1024×768) 60fps、 WXGA(1280×768) 60fps、 WXGA (1280×800) 60fps、 1280×960 60fps、 SXGA(1280×1024) 60fps、 1360×768 60fps、 1366×768 60fps、 1440×900 60fps、 1600×900 60fps、 720P(1280×720) 60fps、 1080P(1920×1080) 24/25/30/50/60fps、 4K(3840×2160) 25/30/50/60fps ; Out: 1920×1080、 3840×2160
Active Double Stream	4K30 + 4K30
Reliability & Security	
Network Adaptability	Video Forward Error Correction (FEC), Packet Loss Retransmission (ARQ) Automatic speed increase and decrease
Security Management	<ul style="list-style-type: none"> • H.235 signaling and media stream encryption(AES-128, AES-256) ; • TLS and SRTP • Administrator password: SSH/HTTPS
Firewall Traversal	H.460, ICE, NAT
I/O	
Video Input Interface	1 × HDMI, Support 4K30fps 1 × HDMI, Support 4K30fps 2 × PSE video network camera input, Max. 4K30fps
Video Output Interface	2 × HDMI, Max. 4K60fps
Audio Input Interface	1 × MINI XLR

*Picture for illustration purpose only



	1 × 3.5mm 2 × RCA 2 × HDMI Audio 1 × DMIC
Audio Output Interface	1 × 3.5mm 2 × RCA 2 × USB 3.0 1 × HDMI Audio
Network Streaming Interface	2 × RJ45
Conference Control Screen Interface	1 × RJ45
COM Interface	1 × RJ45
Network Interface	1 × RJ45 (10/100/1000M LAN)
Conferencing Features	
Language	English
Contacts and Call History	10000 local contacts and call records
Featured Functions	<ul style="list-style-type: none"> • Auxiliary flow accompanying sound; • Infrared penetration; • Time switch; • Support DNS SRV; • Incoming password; • Asymmetric bandwidth; • USB microphone access; • Two or three split screen display; • Network address book; • Built in MCU (optional); • Support web control; • Network upgrade; • Wi Fi access (optional); • RS232/USB serial API control; • Automatic standby and automatic wake-up of incoming calls; • Automatically obtain static NAT addresses; • Picture in Picture (1/16 screen size), Picture beside Picture; • Support third-party integrated development API interfaces;
Generic Spec	
Power	100v~240v AC
Operating Frequency	50Hz/60Hz

*Picture for illustration purpose only