

Wall/Surface Mount Speaker

IT-774H/IT-775H/IT-776H/IT-778H

IT-774HW/IT-775HW/IT-776HW/IT-778HW



Material: plastic

Description:

Indoor high-grade wall/surface mounted speakers, multi-power fixed resistance and fixed pressure selection, modern sense of arc design, 2 frequency division design, high cost performance, convenient installation. Suitable for hotels, conference halls, auditorium, etc.

Specifications:

Model	IT-774H/IT-774HW	IT-775H/IT-775HW	IT-776H/IT-776HW	IT-778H/IT-778HW
Power taps @100V/70V	2.5W, 5W, 10W, 20W	3.75W, 7.5W, 15W, 30W 1.9W	10W, 15W, 20W, 40W, 80W	10W, 15W, 20W, 40W, 80W
Total Power	300W Peak	300W Peak	320W Peak	400W Peak
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
Sensitivity	92dB	92dB	92dB	92dB
Max. SPL(1W/1M)	124dB	124dB	124dB	124dB
Frequency response (-10dB)	65-18KHz	65-18KHz	65-18KHz	65-18KHz
Speaker driver	4" x 1 1.5" x 1	5" x 1 1.5" x 1	6" x 1 0.25mm x 1	8" x 1 1.5" x 1
Nominal Dispersion	90°(H) × 80°(V)	90°(H) × 80°(V)	90°(H) × 90°(V)	90°(H) × 80°(V)
Weight	2.3kg	2.7kg	4.1kg	6.5kg
Protection level	IP65	IP65	IP65	IP65

Note: Images are illustrative purpose only and specification are subject to changes without prior notice for the enhancement of product quality.